

TECHNICAL DATA SHEET

ADSPEC# HM 2501
HOT MELT CARTON SEAL

DESCRIPTION: THIS IS A HOT MELT USED FOR ADHERING DIFFICULT SURFACES. FREEZER GRADE

PHYSICAL PROPERTIES:

TYPE: SYNTHETIC RESIN

VISCOSITY: 850 ± 100 CPS

SPEED OF SET: MEDIUM /FAST SET

HEAT STABILITY: HIGHLY STABLE, NO NOTICEABLE ADVERSE EFFECTS AFTER 100 HRS @350 F (177 C)

APPLICATION: 300-350F
TEMPERATURE

APPLICATORS: EXTRUDER, RESERVOIR PUMP WHEEL SYSTEMS

CLEAN UP: EASY, HEAT AND SCRAPER

STORAGE LIFE: INDEFINITE

SUGGESTED USES: CARTON SEAL /CASE SEAL

PACKAGING: SLATS. PACKED IN DOUBLE WALL CORRUGATED CARTONS LINED WITH POLYETHYLENE PROTECTION.

MACHINE: NORDSON, LTI, GRACO, MERCER UNITS.

FDA STATUS: MEETS COMPOSITION REQUIREMENTS OF INDIRECT FOOD ADDITIVES REGULATION 21 CFR 175.105